



Network Administration HW1

ZSWU

Purposes

- ❑ Building an intranet with DHCP, NAT, VPN, DNS, LDAP, Mail, WWW... services
- ❑ Understanding and managing all these services

HW1 Overview


❑ One “Router”

- Provides NAT, DHCP, VPN
- Connecting your “ClientPC” to the outside world
- Connecting to VPN Server and transfer packets from/to TAs and classmates

❑ One “ClientPC”

- Simulate a simple PC inside the intranet
- Help you verify your results

NA Intranet Schematic Diagram



Requirements (1/4)

❑ “Router”

- You will be arranged a **10.113.x.0/24** subnet by TA for you to do your homework during this semester
 - Don't change your subnet by yourself! Your grade is based on the services in your subnet, and you may crash the whole intranet due to IP collision
- Router must have these three network interfaces
 - **Public** : To Internet
 - Provides NAT on this interfaces, so the packets from the internal network can go to the outside world
 - **Private** : To the internal network
 - Provides DHCP on this interfaces, with IP between **10.113.x.100** and **10.113.x.200**
 - **VPN** : To VPN Server (navpn.nctucs.cc)
 - Send the packets to this interfaces if it's target is **10.113.0.0/16**

Requirements (2/4)

- About VPN
 - Use Wireguard (<https://www.wireguard.com/>)
 - You will get a pre-generated private key and the public key of server for you to connect to navpn.nctucs.cc:51820
 - You can create your own vpn peer so you can connect to your intranet from outside world
- About VM
 - We use Virtualbox by default. You can choose another VM engine or use VPS, but you must satisfy the requirements (Network interfaces, intranet, vpn...etc)
 - With Virtualbox network card settings, you can use “NAT” as the public interface, use “Internal Network” as the private interface
 - Except “Router”, all servers inside the internal network can only have one network interface connect to “Router”, second interfaces on the servers is not allowed

Requirements (3/4)

- Routing and Firewall
 - You may need additional settings for the routing table
 - By default, all the packets from/to 10.113.0.0/16 are allowed
 - By default, the packets from Internet are denied, the packets to Internet are allowed
 - “Router” has two IP address
 - 10.113.0.x/16 on VPN interfaces
 - 10.113.x.254/24 on private interfaces
 - Address on public interfaces are not limited, but make sure it won't impact IPs of the intranet
- About OS
 - You can choose any UNIX-like OS, but make sure it supports all the feature we need
 - We use CentOS by default. Archlinux, Ubuntu and FreeBSD should be fine
 - You can choose different OS for each servers

Requirements (4/4)

❑ “ClientPC”

- This VM can help you debug and verify your results
- You can use any OS on this VM
 - We use Ubuntu by default
 - Linux, BSD, even Windows are allowed
 - GUI is suggested
- Connect to the network by default DHCP client
 - For example, if you use Ubuntu, the network should be connected without any additional configuration
- After all configuration, your “ClientPC” should be able to ping your classmates’ “ClientPC”

DEMO

- ❑ TA will ping “Router” and “ClientPC”
 - Ping 10.113.0.x and 10.113.x.254
 - Ping the IP which “ClientPC” get from the DHCP server
- ❑ Due date: 2019/4/11 18:30

FAQ

- ❑ How to check NAT connectivity?
 - Ping 8.8.8.8 from **ClientPC**
 - Ping www.google.com from **ClientPC**

- ❑ How to check VPN work correctly?
 - Ping 10.113.0.254 from **Router/ClientPC**

- ❑ How to check DHCP work correctly?
 - \$ ip addr or \$ ifconfig
 - Ping **10.113.x.254 (Router)** from **ClientPC**

Help!

- ❑ Email to ta@nasa.cs.nctu.edu.tw
 - Don't send email by E3new
- ❑ EC 3F CSCC